

PRODUCT DATA SHEET

SikaCem® Color

COLOURING AGENT FOR CEMENT, LIME AND PLASTER

DESCRIPTION

SikaCem® Color is a colouring agent in powder form based on mineral oxides.

USES

For colouring cementitious concrete and mortars:

- cementitious renders and screeds ;
- concrete panels ;
- all types of decorative concrete and mortars ;
- for colouring lime/gypsum based renders or plasters.

FEATURES

- Synthetic colouring agent based on mineral oxides
- Good UV stability
- Does not influence the curing time
- Compatible with other SikaCem® products

CERTIFICATES AND TEST REPORTS

CE marking according to EN 12878:2014

PRODUCT INFORMATION

| | | |
|---------------------------|--|------------------------|
| Composition | Mineral oxides | |
| Packaging | A box containing 6 x 1.5 litre plastic canisters | |
| | Colour | Canister weight |
| | Yellow | 400 g |
| | Ochre | 400 g |
| | Blue | 700 g |
| | Black | 700 g |
| | Red | 800 g |
| | Brown | 700 g |
| | Green | 900 g |
| Shelf life | 3 years from date of production | |
| Storage conditions | Store undamaged in dry conditions, protected from direct sunlight and frost, between temperatures +5°C to +30°C. | |
| Bulk density | Colour | Density |
| | Yellow | 0,35 to 0,45 |
| | Ochre | 0,40 to 0,50 |
| | Blue | 0,65 to 0,75 |
| | Black | 0,70 to 0,80 |
| | Red | 0,75 to 0,85 |
| | Brown | 0,75 to 0,85 |
| | Green | 1,00 to 1,10 |

PRODUCT DATA SHEET

SikaCem® Color

August 2024, Version 03.01

02140506100000052

APPLICATION INFORMATION

Recommended dosage Between ½ - 2 canisters per 25 kg of the total binder content depending on the desired colour intensity.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

MIXING

SikaCem® Color is added to the dry mixture. Mix well before adding water.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.